

EVACUATED TUBES

SPECIFICATIONS & SIZING GUIDE

	Size	A-Height (mm)	B-Hot Water Outlet (mm)	C-Cold Water Inlet (mm)	D-Colector (Flow & Sensor Port) (mm)	E-Colector (Return) (mm)	F-PTR Valve (mm)	G-Diameter (mm)	Weight Kilograms (Dry)	
		TANK	200 Litre	1495	1292	74	74	617	1292	540
	250 Litre	1388	1167	74	74	574	1167	648	84	
	315 Litre	1700	1464	74	74	574	1464	648	102	
	400 Litre	1711	1474	74	74	574	1474	730	150	
	Size	Length (mm)	Width (mm)	Depth (mm)	Weight (KG)	Aperture Area (m2)				
	COLLECTOR	20 Tubes	2020	1825	155	77.1	1.86			
		25 Tubes	2020	2240	155	96.1	2.33			
	30 Tubes	2020	2655	155	114.1	2.79				
	Dwelling		System Description			Product Code				
	1-2 Bedroom (1 x Bathroom)		200 Litre 20 Tubes 20LPM			STC-160L-N26-ET20				
	2-4 Bedroom (2 x Bathroom)		250 Litre 25 Tubes 26LPM			STC-250L-N26-ET25				
	4-6 Bedroom (3 x Bathroom)		315 Litre 30 Tubes 26LPM			STC-315L-N26-ET30				
	6+ Bedroom (3 x Bathroom)		400 Litre 40 Tubes 26LPM			STC-400L-N26-ET40				
	Dwelling		System Description			Product Code				
	1-2 Bedroom (1 x Bathroom)		250 Litre 25 Tubes 3.6kW			STC-250L-EO-ET25				
	2-4 Bedroom (2 x Bathroom)		315 Litre 30 Tubes 3.6kW			STC-315L-EO-ET30				
	4-6 Bedroom (3 x Bathroom)		400 Litre 40 Tubes 3.6kW			STC-400L-EO-ET40				

GAS BOOSTER SPECIFICATIONS

Specifications	T Series		RS Series	
	T20	T26	RS20	RS26
Energy Star Rating	6-Star	6-Star	N/A	N/A
Thermal Efficiency	80.5	81.7	N/A	N/A
Rating (l/min @ 25° C rise)	20	26	20	26
Nominal Gas Consumption (MJ/h)	160	193	125	188
Weight (KG)	15.7kg	17.2kg	14.5kg	15.0kg
Height (mm)	530	530	530	530
Height Plus Bracket (mm)	570	570	571	571
Width (mm)	350	350	350	350
Depth (mm)	170	230	194	194
Water Connections Diameter (mm)	20 BSP	20 BSP	20 BSP	20 BSP
Gas Connection Diameter (mm)	20 BSP	20 BSP	20 BSP	20 BSP
Gas Types (Natural Gas / LPG)	NG / LPG	NG / LPG	NG / LPG	NG / LPG
Housing Colour Beige	Beige	Beige	Dune	Dune
Warranty (Heat Exchanger)	10 Years	10 Years	12 Years	12 Years
Warranty (Parts & Labour)	3 Years	3 Years	3 Years	3 Years

WARRANTY

Collector	15 Years
Storage Tank	10 Years
T Series Gas Booster (Heat Exchanger)	10 Years
RS Series Gas Booster (Heat Exchanger)	12 Years
Gas Booster (Parts & Labour)	3 Years
Parts & Labour	1 Year

* Neopower has 140+ registered systems. The systems listed above are our most popular models. Please contact us on 1300 062 788 to discuss a solar hot water solution tailored to your specific needs.

* Warranty policy & T&C's available at www.neopower.com.au