

### SYSTEM OPTIONS

GAS BOOST	Product Code	Tank Capacity	Panel(s)	Booster Options	
	STC-T200L-N26-DL1	200 Litre (316 Grade Stainless Steel)	1 x Large Panel	20LPM	26LPM
	STC-T200L-N26-D2	200 Litre (316 Grade Stainless Steel)	2 x Standard Panel	20LPM	26LPM
	STC-T300L-N26-D2	300 Litre (316 Grade Stainless Steel)	2 x Standard Panel	20LPM	26LPM
ELECTRIC BOOST	Product Code	Tank Capacity	Panel(s)	Booster	Boost Capacity
	STC-T200L-EO-DL1	200 Litre (316 Grade Stainless Steel)	1 x Large Panel	3.6KW	100 Litres
	STC-T200L-EO-D2	200 Litre (316 Grade Stainless Steel)	2 x Standard Panel	3.6KW	100 Litres
	STC-T300L-EO-D2	300 Litre (316 Grade Stainless Steel)	2 x Standard Panel	3.6KW	150 Litres

### HORIZONTAL STORAGE TANK

Tank Capacity (Litres)	Length (mm)	Diameter (mm)	Weight (KG)
200	1488	540	26.5
300	2182	540	37.0

### GAS BOOSTER SPECIFICATIONS

Specifications	T20	T26
Energy Star Rating	6-Star	6-Star
Thermal Efficiency	80.5	81.7
Rating (l/min @ 25° C rise)	20	26
Nominal Gas Consumption (MJ/h)	160	193
Weight (KG)	15.7	17.2
Height (mm)	530	530
Height Plus Bracket (mm)	570	570
Width (mm)	350	350
Depth (mm)	170	230
Water Connections Diameter (mm)	20 BSP	20 BSP
Gas Connection Diameter (mm)	20 BSP	20 BSP
Gas Types (Natural Gas / LPG)	NG / LPG	NG / LPG
Housing Colour Beige	Beige	Beige
Warranty (Heat Exchanger)	10 Years	10 Years
Warranty (Parts & Labour)	3 Years	3 Years

### FLAT PANEL SPECIFICATIONS

	Standard	Large
Length (mm)	2005	2000
Width (mm)	1005	1250
Depth (mm)	90	95
Aperture Area (m2)	1.94	2.35
Weight (KG)	38	41
Glass Type	3.2mm Toughened	3.2mm Toughened

### WARRANTY

Collector	7 Years
Storage Tank	7 Years
Gas Booster (Heat Exchanger)	10 Years
Gas Booster (Parts & Labour)	3 Years
Parts & Labour	1 Year

\* Neopower has 140+ registered systems. The systems listed above are our most popular models.

Please contact us on 1300 062 788 to discuss a solar hot water solution tailored to your specific needs.

\* Warranty policy & T&C's available at

[www.neopower.com.au](http://www.neopower.com.au)